



# LAMBERET



REFRIGERATED ISOTHERMAL BODIES FOR CITROËN  
UTILITY VEHICLES

*2 versions available*  
M (Short, L1) / XL (Long, L2)

*Record volume*  
1.7 m<sup>3</sup> • 11 Eurobox / 2.1 m<sup>3</sup> • 12 Eurobox

*Safety & Comfort*  
Original cab bulkhead retained

 **N° Vert 0 800 308 530**

APPEL GRATUIT DEPUIS UN POSTE FIXE EN FRANCE



[www.lamberet.com](http://www.lamberet.com)

# Berlingo VAN

This body is intended for transport under controlled temperatures, in compliance with the ATP regulations in force.



## BASIC VEHICLE FOR CONVERSION | CITROËN Berlingo

Van with panels, M (L1, wheelbase 2785 mm) or XL (L2, wheelbase 2975 mm), with or without right-hand sliding door, 2 or 3 seats.

With fixed solid cab bulkhead, with panel rear swing doors.

Trailer coupling compatible if fitted before conversion.

Incompatible: 650 kg versions; Worker finish; Options: left-hand side door, ADML hands-free access and starting, work site pack, hinged rear roof flap, tailgate, loading area pack, overload indicator.

### If electric refrigeration unit (positive cold):

1.6 BlueHDI 75 | 100 Euro 6.b, with or without air conditioning; with body pack: available

### If direct-drive refrigeration unit (positive or negative cold):

1.6 BlueHDI 75 | 100 Euro 6.b, with air conditioning, with body pack: **consult us.**

All: without Stop&Start or can be deactivated with body pack. BlueHDI 130 prohibited.

Indicative data – Consult us beforehand to check the compatibility, delivery time and sizing of the refrigeration unit.



## LAMBERET | BODY & INSULATION

ATP-quality “Heightened Insulation” integrated cell formed of a sealed system of single-piece moulded composite panels, **designed and manufactured by Lamberet.**

Hydrophobic polyurethane core with very high insulating power. Non-deformable internal walls coated with white antibacterial gel-coat. Reinforcement of side faces with inserts ready for installing fittings.

Reinforced anti-wear floor in smooth grey gel-coat forming a container with 2 drains in the front.

**Basic equipment:** High brightness LED ceiling light, double seals on openings, side seafood sill, emergency interior unlocking, anti-impact guards on wheel boxes and sills.



## REFRIGERATION UNIT | CARRIER, KERSTNER, THERMOKING, ETC

Positive (Class A) or negative (Class C) cold refrigeration unit.

Power and technology (electric or direct drive) customised depending on use.

Semi-built-in aerodynamic assembly, above the loading area for better soundproofing; digital control on the dashboard.

**Refrigeration unit options:** muffler (compulsory on direct drive), road and sector, heating mode, temperature recorder, “Pharma” certification, refrigeration unit paint. ...

## CONFIGURATIONS | CATERING, DISTRIBUTION, SEAFOOD, HEALTH, ETC.

Aluminium floor coating with plinth rails; corindon non-slip gel-coat floor coating; aluminium plinth rails; aluminium protective rails on side faces; vertical aluminium securing rails with aero-type round perforations (except shelves); horizontal aluminium securing rails with aero-type round perforations (only in combination with shelves); adjustable and height-adjustable shelves, intermediate openwork shelf; rear seafood sill; anti-heat loss curtains.



Carrier | Thermoking semi-built-in refrigeration unit

Kerstner extra-flat refrigeration unit

### Example dimensions (m) \*

Standard wheelbase

	M (L1)	XL (L2)
Standard wheelbase	2.785	2.975
Overall length	4.40	4.75
Usable length: max. on floor   min. in height	1.52   1.31	1.87   1.66
Overall width: with   without rear-view mirrors	2.10   1.92	2.10   1.92
Max. usable width: before   after central pillar (B)	1.35   1.24	1.35   1.24
Width between wheel arches	1.12	1.12
Overall height: isothermal   Kerstner   Carrier - TK	1.79   1.95   1.96	1.81   1.97   1.98
Max usable height excluding evaporator	0.97	0.97
Width   Entrance height between rear doors	1.12   0.97	1.12   0.97
Width   Entrance height of side door	0.46 - 0.51   0.88	0.46 - 0.51   0.88
Loading sill height	Original + 0.09	Original + +0.09
Isothermal fitting weight, excluding refrigeration unit and option (kg)	110	150
Usable volume (m <sup>3</sup> ) - No. Eurobox 600x400x320	1.7   1.1	2.1   1.2

\* Data according to version. Non-contractual document. Pictures may show optional equipment or prototypes. As part of its continual improvement policy, LAMBERET reserves the right to modify the characteristics of conversions without prior notice. Photo credit: LAMBERET SAS – 122018



YouTube

f

in



www.lamberet.com

LAMBERET SAS | Leader in refrigerated utility and industrial vehicles in Europe.

129 route de Vonnas - BP 43 - 01380 Saint-Cyr/Menthon - France | +33 (0)3 85 30 85 30 | communication@lamberet.fr