



Isotherm & refrigerated
Add-on boxes

Sprinter Alko Platform-cabs

Insulated box **NEW FRIGOLINE** from 14m³ to 16 m³

ATP-compliant converted vehicle (certified by CEMAFROID) authorizing the transport of perishable foodstuffs.



Advantages:

Palettizable between wheelcases.

Extra-low access sill, ideal for distribution.

3 body versions taylored to your business needs:

- ❖ NEW FRIGOLINE: attractive, lightweight and ergonomic with "easy-handle" door locks.
- ❖ NEW FRIGOLINE PRO, super-study: buffers, reinforced floor and kickstrips, steel-tripled OT frame.
- ❖ NEW FRIGOLINE BEEF / PRO BEEF: designed and optimized for the transport of hanging meat.



Unique expertise from 1 to 100 m³,
A sales & service network throughout Europe.
> UTAC qualified operator, CEMAFROID manufacturer approval
> Product certification to the ATP and DIN standards,
> Factories ISO 9001 version 2008,
> Product technical specifications incorporating the latest HACCP and NF food standard hygiene initiative,
> CARRIER®, KERSTNER®, EDT®, DELPHI® approved assembly and servicing centre, THERMOKING® partner



Base vehicle :

• Sprinter Alko chassis cab:

- Wheelbase 36 (3510mm) with short cantilever (1410 mm)
Code KAK7ZAW011
- Wheelbase 36 (3510 mm) with medium cantilever (1790 mm) -
Code KAK7ZAW012

• Compulsory or incompatible options:

With front side marker lamps 07

With option code F34

With crankshaft end pulley N63 if there is a refrigeration unit

With 3rd stop light cabling LV6 pre-fixture.

Without blue efficiency pack (EcoStart).

Compatible with air conditioning and BVA

Description of the conversion:

• **NEW FRIGOLINE box** of "Reinforced insulation" quality consisting of panels of a minimum thickness of 85 mm, in gel-coat antibacterial-polyester-polyurethane composite, reinforced with aluminium inserts, designed in accordance with the HACCP hygiene directives.

• **3 int. heights** (2.05 / 2.15 / 2.25m) and **5 rear openings** (OB1 – OB2 – OT2 – OT3 – OR) available.

• As standard:

Rear opening, hinged door OB1 with recessed "easy-handle" 1 handle movement, aluminium mouldings, LED lighting, non-slip floor suitable for pallets between wheel arches with 1 front right run-off drain, aluminium plinths on 3 faces including protection stringers on wheel arches, partial rear step, side lights.

Refrigeration unit:

Positive cooling unit (class A) or **negative** (class C) installed on the front face or in a "recess".

Direct drive technology, power rating according to use.

Options: mains, heating, multi-temperature, temperature recorder, deflector.

Conversion options and packs:

• **"PRO pack"** with **OB1** or option **OB2**: reinforced floor + alu. plinths HD + reinforced seal angle bars on plinths.

• **"PRO pack"** with option **OT [full opening]**: reinforced floor + alu. plinths HD + reinforced seal angle bar on plinths + triple thickness frame in THLE steel / aluminium / stainless steel + full length and width sill buffers + 2 buffers on vertical posts + 2 buffers with recessed rear side marker lights if the vehicle is fitted with this option.

• **"BEEF pack"**: dedicated to the transport of hung meat; roof with insulated inserts in steel in 610 mm steps, pre-fixed for meat hanging.

• **"PRO BEEF pack"**: a combination of the "PRO" and "BEEF" packs, a consolidated transport solution for transporting hung meat.

Options:

Rear access with 2 hinged doors (OB2) with integrated locking gear, or full rear opening with 2 (OT2) or 3 (OT3) door leaves on a reinforced frame with external locking gear (**OT / full opening only with modified width 2.09 ext.**)

Hinged side door (900 x hi, position from 100 mm from the front). Partition for multi-temperature vehicle, adjustable & foldable shelving, rails, stringers, Interinox, meat hanging system (on BEEF and PRO BEEF), fish handling equipment.

Indicative masses/dimensions (mm)	w/b. 3510 mm	w/b. 3510 mm
Base vehicle cantilever	Short 1410 mm	Medium 1790 mm
Overall length	6490	6790
Overall width (rear OB/OT)	2200/2090	2200/2090
Overall height	2845	2845
Usable length (if OT: -24 mm.)	3504	3804
Usable width (rear OB/OT [hinged/full opening])	2015/1915	2015/1915
Width between wheelcases	1400	1400
Usable height	2050	2050
Threshold height	680	680
Estimated usable volume m ³	14 m³	16 m³
Mass veh. + insulation (kg)	NC	2680



"Easy-handle" 1 movement grip handle



Side fold-away step (option)



Fixed partial rear step



Rear opening OB1 (as standard)



Rear opening OT2 PRO (option with reduced width 2.09 ext./1.91 int.)

Non-contractual document. Visual may show optional equipment items. In the context of its continual improvement policy, LAMBERET reserves the right to modify the characteristics of these conversions without notice. Photo credits: LAMBERET SAS – REV. 01/2016.



CONSEIL FROID VU

N°Vert 0 800 308 530

APPEL GRATUIT DEPUIS UN POSTE FIXE EN FRANCE

