



# Refrigerated & Isotherms Add-on boxes

## Vivaro Platform-cab

insulated box **NEW FRIGOLINE** from 10 m<sup>3</sup> to 11m<sup>3</sup> on platform-cabs

ATP-compliant converted vehicle (certified by CEMAFROID) authorizing the transport of perishable foodstuffs.



### Advantages: 3 body types tailored to suit your business needs

- ❖ **NEW FRIGOLINE**: attractive, lightweight, and ergonomic, with « easy-handle » door locks.
- ❖ **NEW FRIGOLINE PRO**, super-sturdy: reinforced buffers, floor, and kickstrips, steel-tripled OT frame.
- ❖ **NEW FRIGOLINE BEEF / PRO BEEF**: designed and optimized for the transport of hanging meat.



A single design from 1 to 100m<sup>3</sup>,  
A sales & service network throughout Europe  
> UTAC-qualified operator, CEMAFROID manufacturer certification  
> Product certification to ATP and DIN standards  
> Factories compliant with ISO 9001 version 2008  
> Product specifications include the HACCP hygiene policy and NF food safety standards  
> Approved assembly and installation center for CARRIER®, KERSTNER®, and EDT®, partner of THERMOKING®



**Basic vehicle:**

**Vivaro flatbed**

L2H1 – wheelbase 3498 mm

**Required or unavailable options:**

With "medium stick" rear-view mirrors

No Stop&Start.

No air conditioning, no automated gearbox, with power take-off (all diesel)

With air conditioning, without power take-off available on 2.0 CDT115.

PULSOR: No kit available.

**Description of the conversion:**

• **NEW FRIGOLINE cell** , "High-Insulation" quality, made of antibacterial polyester-polyurethane gel-coat composite panels at least 85 mm thick, fitted with aluminum inserts, designed to HACCP hygiene directives.

• **4 inner heights** (1.80 / 1.95 / 2.05 / 2.15m) and **5 types of rear door arrangements** (OB1 – OB2 – OT2 – OT3 – OR) available

• **Standard:**

1-panel OB1 rear door with recessed 1-motion « easy handle », aluminum molding, LED lightning inside, non-skid floor with wheel arches and 1 front right drainage channel, three-sided aluminum kickstrips including protective runners on wheel arches, partial rear foot-step, sidelights if overall length is longer than 6 meters.

**Refrigeration unit:**

**Above-zero unit**(class A) or **sub-zero unit** (class C), placed on front face Pulley-engine technology, power based on use

**Options:** sector, heating, multi-temperature, temperature recorder, spoiler.

Dimensions (mm) / Versions	L2H1 Hi 1800	L2H1 Hi 1950	L2H1 Hi 2050	L2H1 Hi 2150
Wheelbase	3498			
Outer length	5682			
Cell length	2924 (OB) / 2900 (OT)* Special Version coupling: 2844 (OB) / 2850 (OT)			
Usable length	2754 (OB) / 2730 (OT)*			
Max usable width	1917			
Overall width	2093			
Wheel arch width	1204			
Max usable height	1800	1950	2050	2150
Total outer height	2506	2656	2756	2856
Estimated usable volume in m³	9,5	10,3	10.8	11.3
Mass of insulation	490	510	540	580

\*Full opening (OT) optional

**Conversion options and packages:**

**Packages:**

• **"PRO"** with **OB1** or optionally **OB2**: Reinforced floor + HD aluminum kickstrips + high-tightness brackets at kickstrips corners.

• **"PRO"** with **OT** option: Reinforced floor + HD aluminum kickstrips + high-tightness brackets at front kickstrips corners + triple-thick VHYS steel/aluminum/stainless steel frame + threshold protection along entire length and height + 2 buffers on vertical risers + 2 buffers in which rear outline marker lights are embedded if the vehicle has them as an option.

• **"BEEF"**: with insulated steel inserts every 610mm, suitable for fastening hangers Hanging meat transport solution.

• **"PRO BEEF"** Combination of PRO and BEEF packages, reinforced hanging meat transport solution..

**Options:**

Two-panel swinging rear door (OB2) with integrated door-locks, or full rear door with 2 (OT2) or 3 (OT3) panels on reinforced bolted frame with external door-locks.

Side swinging door (900 x IH, position from 100 mm of the rear). Bulkhead for multi-temperature vehicle, adjustable and liftable shelves, rails, runners, Interinox fasteners, meat hangers (on BEEF and PRO BEEF) with fish accessories.



On OT2, Pro Package: Triple stainless steel vertical risers on frame



Interinox + rails + hangers option



On OT/Pro Package: reinforced stops



OT2 option, bolted rear frame



1-motion "easy" handle



OB1 opening

This document is for information purposes only. Images may depict optional features. As part of its continuous improvement policy, LAMBERET reserves the right to alter the characteristics of the conversions without prior notice. Photo credit: LAMBERET SAS – 07/2016.

-20 C° -18 C° -14 C° -12 C° -10 C° -8 C° -6 C° -4 C° -2 C° -0 C°



LAMBERET SAS  
129 Rte de Vonnas – F-01380 ST-CYR/MENTHON  
Tel +33 (0)3 85 30 85 30  
E-Mail: [communication@lamberet.fr](mailto:communication@lamberet.fr)  
[www.lamberet.com](http://www.lamberet.com)

